



User-friendly Meets Mobility

The Vivitek D330MX digital projector is mobile yet powerful enough to handle today's multimedia and video applications. With 3000 lumens, 2500:1 contrast ratio and a quick on/off feature, the D330MX becomes an essential presentation tool. With multiple connectivity options, a built-in speaker and DLP®/BrilliantColor™ technologies, the Vivitek D330MX delivers consistently sharp, vivid images. The Vivitek D330MX is portability made simple.

Features

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Enhanced color and display adjustments
- 3000 lumens of brightness with a 2500:1 contrast
- Keypad lock feature to avoid accidental changes to the settings
- Lightweight at 3.2 pounds
- Up to 3000 hours of lamp life

Specifications	
Brightness	3000 Lumens
Native Resolution	XGA (1024 x 768)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	2500:1 (Full On/Off)
Lamp Life and Type	≈2000/3000 Hours (Standard/Economy Mode), 220W
Lamp Part #	TBD
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio	1.9 to 2.2:1 (Distance/Width)
Image Size (Diagonal)	34" to 300" (0.9 to 7.6 m)
Projection Distance	4.9' to 32.9' (1.5 to 10.0 m)
Projection Lens	F= 2.5, f= 21.3 ~24.5 mm
Zoom Ratio	1.15:1 Manual Zoom/Focus
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	128%
Keystone Correction	±15° Vertical
Color Spectrum	134 Million
Horizontal Scan Rate	15, 30 to 91.4 KHz
Vertical Scan Rate	43 to 87 Hz
Speaker	1 Watt Mono
Remote Control	Card-Type IR Remote
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, L, L)
I/O Connection Ports	VGA-In, S-Video, Composite Video, Mini-Jack Audio-In, USB (Service)
Security	Kensington® Lock Port
Weight	3.2 lbs (1.45 kg)
Dimensions (W x H x D)	8.66" x 2.8" x 7.0" (220 x 71 x 178 mm)
Noise Level	32dB/30dB (Standard/Economy Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: 230W (Economy Mode), 280W (Standard Mode), <1W (Standby Mode)
Operating Temperature	41 to 95°F (5 to 35°C)
Warranty	1-Year Limited Warranty, 90-Day Lamp Warranty
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual (CD), Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case
UPC	8 14964 33509 8

